



## Declaration of Performance (DoP)

No. F520-CPR-150418	
<b>Product Type:</b>	Roomheaters fired by solid fuel
<b>Type, batch or serial number:</b>	<b>Jøtul F 520</b>
<b>Intended use of the product:</b>	Roomheater burning solid fuel without water supply
<b>Name and Address of the manufacturer:</b>	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
<b>AVCP:</b> <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
<b>Notified body:</b>	Danish Technological Institute
NB-No:	1235
Test report no:	300-ELAB-1835-EN
<b>Declared performance:</b>	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fuel	Wood logs
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm Rear = 300 Sides = 700 Corner = 600 Front = 900 <i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,07 %] NOx [54 mg/m <sup>3</sup> ] OGC [60 mgC/m <sup>3</sup> ] PM [14 mg/m <sup>3</sup> ]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [305°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	7 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [77%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager


---

(Name and function)

Fredrikstad      April 18, 2015

---

(Place and date of issue)



---

(Signature)